

LUKOIL ANTIFREEZE HD LONG LIFE

Coolant for heavy-duty equipment with extended drain interval

Specifications

- CAT ELC (EC-1)
- Cummins 90T8-4
- Detroit Diesel 7SE298
- Freightliner 48-22880
- GM 1825/1899M/6277M
- ASTM D3306/D6210/D4985
- SAE J1034
- TMC RP329
- PJSC «Tutaevsky Motor Plant»
- PJSC «Avtodiesel» (YaMZ)
- PJSC «KAMAZ»
- URAL
- LiAZ
- PJSC «Rostselmash»

Product description

Ready-to-use high quality coolant. Formulated with ethylene glycol and a hybrid anti-corrosion additive package. Contains nitrites and molybdates to protect wet cylinder liners from cavitation wear. It has a balanced chemical composition of corrosion inhibitors, a limited amount of silicates and does not contain phosphates, which prevents the formation of scale and sediment.

Application

Intended for use in closed cooling systems of engines of passenger cars and commercial vehicles.

Benefits

EXTENDED DRAIN

Extends drain interval due to unique combination of corrosion inhibitors

RELIABLE PROTECTION

Reduces repair and maintenance costs of cooling systems

The product name in an order: Coolant LUKOIL ANTIFREEZE HD LONG LIFE, STO 79345251-008-2008

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Color	GOST 28084, 4.1	From pink to violet
Density at 20 °C, kg/m ³	GOST 18995.1	1,075
Crystallization temperature, °C	GOST 28084	-40
Boiling temperature, °C	p.7.3 STO	109
pH at 20 °C	GOST 22567.5	8