

LUKOIL ANTIFREEZE G12++

Engine coolant with low pour point

Specifications

- VW TL 774-G
- ASTM D3306/D4985
- AS 2108-2004
- ONORM V5123
- BS 6580
- CUNA NS 956-16
- SAE J1034
- China GB 29743-2013

Product description

Ready-to-use premium coolant. Developed on the basis of hybrid organic acid technology ("lobrid" technology - "Si-OAT"). Provides effective protection against freezing, overheating and corrosion.

Application

Recommended for all-season use in closed cooling systems of modern engines of most cars and trucks.

The product name in an order: Coolant LUKOIL ANTIFREEZE G12++, STO 79345251-008-2008

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

| Property | Test methods | Value |
|--|-----------------|---------------------|
| Color | GOST 28084, 4.1 | From pink to violet |
| Density at 20 °C, kg/m ³ | GOST 18995.1 | 1,079 |
| Crystallization temperature, °C | GOST 28084, 4.3 | - 40 |
| pH at 20 °C | GOST 22567.5 | 8 |
| Corrosive impact on metals, g/m ² day | | |
| - cuprum | | 0,08 |
| - brass | | 0,08 |
| - aluminum | GOST 28084, 4.5 | 0,05 |
| - steel | | 0,03 |
| - solder | | 0,07 |