

## LUKOIL AIR 100

### Industrial oil for pneumatic tools

#### Product description

High quality industrial oil designed for lubrication of pneumatic tools of drilling and percussion type. Specially selected base oils and additives provide a high level of adhesion, anti-corrosion and anti-wear properties and reliable operation of equipment in a wide range of temperatures and loads.

#### Benefits

##### RELIABLE PROTECTION

High oil film thickness over entire drain interval

The product name in an order: Industrial oil LUKOIL AIR 100, STO 79345251-373-2023

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	876
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	11.0
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	94.9
Flash Point, COC, °C	ASTM D92	257
Tribological properties on four-ball machine: -Wear scar diameter, mm	GOST 9490	0.33
Pour Point, °C	GOST 20287 B	-25
Copper corrosion (3 h, 100°C)	ASTM D130	1b