

## LUKOIL GEYSER LT 32

### Multigrade hydraulic oil

#### Specifications

- Bosch Rexroth RDE 90235
- Denison HF-0/HF-1/HF-2
- Kopex Machinery
- Palfinger
- Sulzer Pumps
- DIN 51524-3 (HVLP)
- ASTM D6158 HV
- GM LS-2
- AGMA 9005-E02
- Mantsinen
- Amco Veba
- Eaton Vickers 35VQ25
- METSO
- SMT Scharf
- ThyssenKrupp Industrial Solutions
- ISO 11158 (HV)
- SAE MS 1004
- AIST 126/127
- Eaton Vickers E-FDGN-TB002-E
- Fives Cincinnati P-68

#### Product description

Multigrade hydraulic oil with excellent flow characteristics especially at low temperatures. This oil offers improved oxidative stability and low temperature, antiwear, anticorrosion and foam suppression properties. It is especially effective in hydraulic systems where only negligible viscosity changes are allowed within wide range of operation temperatures.

#### Application

Recommended for use in hydraulic systems of mobile equipment, forest machines, road machinery, forklifts and cranes. The oil is also applicable for hydraulic systems of stationary equipment which operates in unheated rooms or outdoor year-round where oil with stable viscosity-temperature properties are required.

#### Benefits

##### YEAR-ROUND OPERATION

Low temperature dependence of viscosity (high viscosity index) and good low temperature properties

##### WEAR PROTECTION

Provides superior antiwear properties

The product name in an order: Hydraulic oil LUKOIL GEYSER LT 32, TU 0253-010-79345251-2008

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	847
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	31.7
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	6.2
Kinematic viscosity at -20 °C, mm <sup>2</sup> /s	ASTM D445 / GOST 33 / GOST R 53708	1,335
Viscosity index	ASTM D2270	149
Flash Point, COC, °C	ASTM D92	236
Foaming (tendency/stability):	ASTM D892	
-at 24 °C, ml		5/0
-at 94 °C, ml		10/0
-at 24 °C after test at 94 °C, ml		10/0
Pour Point, °C	GOST 20287 B	below -40