

LUKOIL LUXE 5W-30

Semi-synthetic engine oil

Specifications

- API SL/CF
- JSC «AVTOVAZ»
- PJSC «ZMZ»

Product description

High-quality semi-synthetic engine oil. Produced using a highly effective additive package.

Application

Intended for use in gasoline and diesel engines of passenger cars, vans and light trucks, where API SL/CF performance level is required.

Benefits

OXIDATION RESISTANCE

Superior oxidation stability

EXCELLENT CLEANLINESS

Prevents the formation of high and low temperature deposits on engine components

The product name in an order: Multigrade Engine Oil LUKOIL LUXE semi-synthetic SAE 5W-30, API SL/CF, STO 00044434-003-2005

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	875.5
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.9
Viscosity index	ASTM D2270	160
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	6,082
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	28,100
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.6
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	12
Flash Point, COC, °C	ASTM D92	223
Pour Point, °C	GOST 20287 B	-42