

## LUKOIL TEp-15

Transmission oil of API GL-2 level for tractors and agricultural machinery

### Specifications

- API GL-2

### Product description

All-season transmission oil based on mineral oil and additives that improve anti-wear and low-temperature properties.

### Application

Used as an all-season transmission oil for cylindrical, conical and helical-conical gears of tractors and other types of agricultural machinery, as well as for various machines and mechanisms that require API GL-2 level. The oil is intended for the operation of machinery in areas with a temperate climate.

### Benefits

#### WEAR PROTECTION

Reliable operation of transmission units in temperate regions under medium and high loads

#### OXIDATION RESISTANCE

Provides stable properties during whole period of operation

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Viscosity class	SAE J 306	90
Density at 20 °C, kg/m <sup>3</sup>	GOST 3900	919.6
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	GOST 33	14.9
Dynamic viscosity at -15 °C, Pa·s	GOST 1929	49
Flash Point, COC, °C	GOST 4333	236
Pour Point, °C	GOST 20287 B	- 19