

LUKOIL GENESIS SPECIAL RN 5W-30

Synthetic engine oil for the newest Renault engines

Approvals

- Renault RN17

Meets requirements

- ACEA C3

Product description

Multigrade fully synthetic Mid-SAPS engine oil, specially developed on the basis of modern synthetic base oils and a high-performance additive package with a reduced content of sulfur, phosphorus and sulphated ash for the latest generation of Renault gasoline and diesel engines.

Application

Recommended for use in modern gasoline and diesel engines equipped with exhaust aftertreatment systems - Diesel Particulate Filters (DPF) and Three Way Catalytic Converter (TWC), where the use of oils that meet the latest Renault RN17 specification. Also can be used in engines where Renault RN 0700/0710 specification is required.

Benefits

COMPATIBILITY WITH AFTERTREATMENT SYSTEM

Compatible with exhaust aftertreatment devices, which are sensitive to sulphated ash content

ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

MAXIMUM PROTECTION

Adjusted for severe conditions of urban cycle

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL RN 5W-30, STO 79345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	62.1
Viscosity index	ASTM D2270	187
Flash Point, COC, °C	ASTM D92	230
Pour Point, °C	GOST 20287 B	-44
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	11.7
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.6
Sulphated ash, %	ASTM D874	0.78
Density at 20 °C, kg/m ³	ASTM D4052	847