

LUKOIL GENESIS SPECIAL C1 5W-30

Synthetic engine oil with Low SAPS content

Specifications

- ACEA C1
- Jaguar Land Rover ST JLR.03.5005

Product description

Synthetic engine oil with extremely low-ash content for modern Jaguar Land Rover passenger cars, including equipped with aftertreatment devices (DPF).

Application

Specially developed for all-season use in new generation of Jaguar and Land Rover engines requiring ST JLR.51.5005 specification. Also suitable for use in certain Mazda engines requiring ACEA C1 specification and 5W-30 viscosity grade.

Benefits

COMPATIBILITY WITH AFTERTREATMENT SYSTEM

To increases service life of aftertreatment devices due to low ash

LSPI PROTECTION

Protects against LSPI (Low Speed Pre Ignition) phenomenon, which occurs in TGD (Turbocharged gasoline direct injection) engines

FUEL ECONOMY

Superior fuel economy thanks to lower HTHS viscosity and potential to reduce emissions

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	847
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	9.6
Viscosity index	ASTM D2270	177
Sulphated ash, %	ASTM D874	0.5
Flash Point, COC, °C	ASTM D92	210
Pour Point, °C	GOST 20287 B	-40