

## LUKOIL GENESIS SPECIAL C2 5W-30

Fully synthetic Mid SAPS motor oil

### Specifications

- ACEA C2, A5/B5, A1/B1
- PSA B71 2290
- Fiat 9.55535-S1
- API SN/CF
- Renault RN 0700
- Iveco 18-1811 SC1

### Product description

Synthetic motor oil for gasoline and diesel engines of passenger cars. Produced from high quality synthetic base oils with the use of advanced additive technology with a reduced sulphated ash content. Recommended for car service in service stations.

### Application

Recommended for all-season use in modern gasoline and diesel engines of Peugeot-Citroen vehicles that require PSA B71 2290 oils. Also recommended for use in engines of Japanese and Korean cars, including Toyota, Kia, Infiniti, Suzuki, Subaru and others, where ACEA C2 quality level is required.

### Benefits

#### EASY START

Excellent low-temperature pumpability

#### MAXIMUM PROTECTION

Maximum protection against wear at severe conditions of urban driving cycle

#### COMPATIBILITY WITH AFTERTREATMENT SYSTEM

Compatible with exhaust aftertreatment devices, which are sensitive to sulphated ash content

#### FUEL ECONOMY

Superior fuel economy thanks to lower HTHS viscosity and potential to reduce emissions

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL C2 5W-30, STO 79345251-074-2015

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	847.3
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	11.0
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	62
Viscosity index	ASTM D2270	171
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	4,470
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	16,800
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.0
Sulphated ash, %	ASTM D874	0.8
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	10
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	GOST 20287 B	-46