

LUKOIL GENESIS SPECIAL RACING 10W-60

Fully synthetic high performance engine oil

Specifications

- ACEA A3/B3, A3/B4
- API SN
- Fiat 9.55535-H3

Product description

High performance top level engine oil, specially developed for 4-stroke engines operating under extremely severe conditions of racing competitions. Provides optimum lubrication even at highest engine revolutions and maximum temperatures, allows maximum engine output and protects against wear.

Application

Recommended for all-season use in highest performance engines and meets the demands of professional racing competitions. Offers excellent oil film stability and optimal lubrication at extremely high engine revolutions.

Benefits

OXIDATION RESISTANCE

Improved oxidation stability due to well balanced combination of high alkalinity reserve additives package and PAO base oils

EXREMELY HIGH LOADS

Designed for gasoline sport cars running under extreme load conditions

PERFECT PROTECTION

Perfect protection of turbocharged engines of cars operating at racing high load conditions

ENGINE CLEANLINESS

Great dispersant and detergent properties prevent deposits formation on engine parts

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D4052	857
Flash Point, COC, °C	ISO 2592	250
Kinematic viscosity at 40 °C, mm ² /s	DIN 51562/T1	126.9
Kinematic viscosity at 100 °C, mm ² /s	DIN 51562/T1	22.2
Viscosity index	ISO 2909	204
Pour Point, °C	ISO 3016	<-36