

LUKOIL GENESIS SPECIAL VL 0W-20

Fully synthetic engine oil

Specifications

- API SP
- ACEA C5
- VOLVO VCC-RBSO-2AE
- Fiat 9.55535-DSX

Product description

Multigrade fully synthetic engine oil of the last generation with high fuel economy and excellent low-temperature properties.

Application

Recommended for use in 4-cylinder gasoline and diesel engines of passenger cars operated under severe conditions and which require the use of oils with VOLVO VCC RBSO-2AE specification. Also can be used in cars where ACEA C5 and/or API SP quality level is required.

Benefits

EASY COLD START

Excellent low-temperature properties provide easy cold start

MAXIMUM PROTECTION

Maximum protection against wear at severe conditions of urban driving cycle

COMPATIBILITY WITH AFTERTREATMENT SYSTEM

Low content of sulphated ash, phosphorus and sulphur ("Mid SAPS") reduces inorganic sludge in DPF and catalysts

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL VL 0W-20, STO 79345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	839.4
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	8.46
Viscosity index	ASTM D2270	178
Dynamic viscosity (CCS) at -35°C, mPa·s	ASTM D5293 / GOST R 52559	4,200
Total Base Number, mg KOH/1 g oil	ASTM D2896	9.0
Flash Point, COC, °C	ASTM D92	227
Pour Point, °C	ASTM D97	-50