

LUKOIL ATF

Semi-synthetic automatic transmission fluid

Specifications

- GM Dexron IIIG/IID
- ZF-TE-ML 04D/14A/11A/11B/17C
- BELAZ
- Caterpillar TO-2
- RBAS TE-ML 09
- VOITH H55.6335.XX
- MAN 339 Z1/L1/V1
- Allison C-4
- VOLVO 97341/97340
- MAN 339 Type D/Type F

Product description

Universal semi-synthetic automatic transmission fluid designed for both passenger cars and heavy duty applications to meet and exceed the requirements of the world's leading original equipment manufacturers.

Application

Designed for use in step-type automatic transmissions of passenger cars and commercial vehicles, where recommended fluid specification is Dexron IIIG or below. It can also be used as a power steering fluid.

Benefits

ALL SEASONS PROTECTION

Excellent low-temperature properties - seasonal oil change is not required

OXIDATION RESISTANCE

Excellent resistance to oxidation and corrosion

PROTECTION OF HIGH-MILEAGE TRANSMISSIONS

Effective protection of transmission components through the use of a modern additive package with an increased rate of anti-wear properties

The product name in an order: Automatic transmission fluid LUKOIL ATF, STO 79345251-362-2023

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Appearance	–	Transparent red fluid
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	7.5
Viscosity index	ASTM D2270	178
Dynamic viscosity at -40 °C, mPa·s	ASTM D2983	11,600
Flash Point, COC, °C	ASTM D92	203
Pour Point, °C	GOST 20287 B	– 50