

## LUKOIL GEAR GL-4/5 75W-90

Synthetic transmission oil compliant with API GL-4/5

### Specifications

- API GL-4 / GL-5 / MT-1
- DTFR 12B100 (MB 235.0)
- Scania STO 1:0
- SAE J2360
- ZF TE-ML 02B/04G/05A/05B/07A/08/17B
- MIL-PRF-2105 E

### Product description

Universal transmission oil for manual transmissions, differentials and final drive.

### Application

Intended for universal use in manual transmissions, differentials, final drives, drive axles and transfer cases of passenger cars, light commercial vehicles and trucks.

Not recommended for use in automatic transmissions and limited-slip differentials (LSD)

### Benefits

#### VERSATILITY OF APPLICATION

Versatility of application allows to reduce costs and unify warehouse storage

#### HIGH PROTECTIVE PROPERTIES

Enhanced protection of transmission components and excellent compatibility with any type of synchronizers due to the use of a balanced additive package

#### EXTENDED DRAIN INTERVAL

Extended replacement interval and reliable operation of transmission units due to the use of proprietary high-quality base oils

The product name in an order: Transmission oil LUKOIL GEAR GL-4/5 75W-90, STO 79345251-363-2023

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	866
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	16.3
Dynamic viscosity at -40 °C, mPa·s	ASTM D2983	55,950
Viscosity index	ASTM D2270	203
Pour Point, °C	GOST 20287 B	-46
Flash Point, COC, °C	ASTM D92	210