

LUKOIL VERSO 10W-30

Universal Tractor Transmission Oil (UTTO)

Specifications

- API GL-4
- Massey Ferguson CMS M1135/M1143
- Sauer Sunstrand/Danfoss Hydro Static
- CNH MAT 3525
- KUBOTA UDT
- Valtra G2-08
- Ford ESN-M2C86-A
- White Q-1705/1722/1766/1766B/1802/1826
- JCMAS HK P-041
- Eaton Vickers E-FDGN-TB002-E
- Allison C-4
- Caterpillar TO-2
- Fiat AF 87
- CASE MS 1204/1207/1209
- Ford ESN-M2C134-D/ESN-M2C86-B
- NH 410B/420A
- I.H.C. B5 & B6 Hydran
- Oliver Type 55/Type5J/Q1802
- Denison HF-0/HF-1/HF-2

Product description

Universal Tractor Transmission Oil (UTTO), designed for use in combined hydraulic-transmission-wet braking systems of agricultural equipment.

Application

Recommended for use in transmissions, hydraulic and oil-immersed brakes, other ancillary systems fitted to tractors and agricultural machinery.

Benefits

EXCELLENT ANTI-WEAR PROPERTIES

Effectively protects transmission units from wear

HIGH OXIDATION STABILITY

Extends the transmission's service life during the whole drain interval

VERSATILITY

Suitable for use in most types of machinery

The product name in an order: Universal tractor oil LUKOIL VERSO SAE 10W-30, STO 79345251-022-2009

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D4052	867.7
Kinematic viscosity at 100 °C, mm ² /s	ASTM D7042 / ASTM D445	9.9
Flash Point, COC, °C	ASTM D92	242
Viscosity index	ASTM D2270	134
Brookfield viscosity at -35 °C, mPa·s	ASTM D2983	44,550
Pour Point, °C	GOST 20287 B	-47