

LUKOIL VERSO PLUS

Universal Tractor Transmission Oil (UTTO)

Specifications

- John Deere JDM J20C
- Massey Ferguson CMS M1135/M1143/M1145
- CASE MS 1204/1206/1207/1209
- API GL-4
- Sauer Sunstrand/Danfoss Hydro Static
- CNH MAT 3525
- KUBOTA UDT
- Valtra G2-08
- Ford ESN-M2C86-A
- White Q-1705/1722/1766/1766B/1802/1826
- Allison C-4
- Caterpillar TO-2
- Fiat AF 87
- Ford ESN-M2C134-D/ESN-M2C86-B
- NH 410B/420A
- I.H.C. B5 & B6 Hydran
- Oliver Type 55/Type5J/Q1802
- Denison HF-0/HF-1/HF-2
- Eaton Vickers E-FDGN-TB002-E
- JCMAS HK P-041

Product description

Universal Tractor Transmission Oil (UTTO) specially formulated to provide the best lubrication for transmissions of combined hydraulic-transmission-wet braking systems in agricultural equipment. Meets the requirements of leading manufacturers of modern equipment. Suitable for use in harsh operating conditions.

Application

Recommended for use in transmissions, hydraulic and oil-immersed brakes, other ancillary systems fitted to tractors and agricultural machinery of world leading manufacturers.

Benefits

SMOOTH OPERATIONS

Provides smooth operation of oil-immersed brakes, low noise and vibration levels.

LONG SERVICE LIFE

High share stability provides long-term and reliable operation of transmission units in harsh operating conditions and in a wide temperature range.

EXCEPTIONAL OXIDATION STABILITY

Extends life and performance even under some of the harshest conditions.

The product name in an order: Universal tractor oil LUKOIL VERSO PLUS, STO 79345251-022-2009

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D4052	878.7
Kinematic viscosity at 100 °C, mm ² /s	ASTM D7042 / ASTM D445	9.91
Flash Point, COC, °C	ASTM D92	230
Viscosity index	ASTM D2270	130
Brookfield viscosity at -35 °C, mPa·s	ASTM D2983	50,450
Pour Point, °C	GOST 20287 B	-50