

LUKOIL LUXE SPECIAL 5W-40

Multi-grade fully synthetic motor oil of the latest generation

APPROVALS

API SN - licensed (API №2523)
MB-Approval 229.5
Renault RN 0700 / 0710
VW 502 00 / 505 00

MEETS REQUIREMENTS

API CF
ACEA A3/B4, A3/B3

PRODUCT DESCRIPTION

LUKOIL LUXE SPECIAL 5W-40 is multi-grade fully synthetic motor oil with API SN/CF, ACEA A3/B4 performance levels. It is formulated on high-quality synthetic base oil and advanced additive technology. Recommended for service maintenance at service stations.

APPLICATION

LUKOIL LUXE SPECIAL 5W-40 is intended for use in modern gasoline and diesel engines including turbocharged ones.

The product name in an order:

Multigrade Engine Oil LUKOIL LUXE SPECIAL 5W-40, STO 79345251-074-2015

BENEFITS

- Reliable engine protection in severe conditions of winter due to improved low-temperature properties
- Prevents the formation of high- and low-temperature deposits on engine components
- Excellent protection from wear
- Adjusted for severe conditions of urban cycle

TYPICAL TEST DATA

| PROPERTY | Test methods | LUKOIL LUXE SPECIAL 5W-40 |
|---|--|---------------------------|
| Density at 15 °C, kg/m ³ | ASTM D1298 / GOST R 51069 / ASTM D4052 | 845 |
| Kinematic viscosity at 100 °C, mm ² /s | ASTM D445 / GOST 33 / GOST R 53708 | 13.2 |
| Viscosity index | ASTM D2270 / GOST 25371 | 180 |
| Apparent viscosity CCS at -30 °C, mPa·s | ASTM D5293 / GOST R 52559 | 3,672 |
| Apparent viscosity MRV at -35 °C, mPa·s | ASTM D4684 / GOST R 52257 | 29,350 |
| Total base number, mg KOH/1 g oil | ASTM D2896 / GOST 30050 | 10.5 |
| Sulphated ash, % | ASTM D874 / GOST 12417 | 1.2 |
| Noack evaporation loss, % | ASTM D5800 / DIN 51581-1 | 9.7 |
| Flash Point, COC, °C | ASTM D92 / GOST 4333 | 222 |
| Pour Point, °C | GOST 20287 B | -40 |

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".

v1.2_01.06.2016* Page 1/1

* This document supersedes all previous versions

Malaya Yakimanka,
 119180 Moscow, Russia
 Tel.: (495) 627-40-20
 Fax: (495) 981-76-84
 www.lukoil-lubricants.com
 member of::

//