

LUKOIL GENESIS SPECIAL C2 0W-30

Multi-grade low SAPS fully synthetic diesel engine oil

MEETS REQUIREMENTS

ACEA C2
PSA B71 2312

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL C2 0W-30 is multi-grade fully synthetic motor oil of the last generation for all modern passenger cars and light trucks, which require usage of low-viscous low-SAPS lubricants with robust anti-friction properties.

APPLICATION

The product is recommended for Peugeot-Citroen cars equipped with gasoline engines with volume up-to 1.8 litre and diesel engines with diesel particulate filter with volume up-to 3.0 litre, except of 1.3 litre and 2.2 litre (customization of 204 horse power); and for vehicles of any other manufacturers, which demands lubricants according ACEA C2 and SAE 0W-30.

The product name in an order:

Motor oil LUKOIL GENESIS SPECIAL C2 0W-30

The product is manufactured in Austria

FEATURES AND BENEFITS

- Easy start-up at low temperatures
- High resistance to oxidation and robust anti-friction properties
- The best wear protection of engine in severe conditions of city-cycle
- High index of fuel economy
- Compatible with exhaust systems which sensitive to sulphated ash content
- Suits to engine operation under heavy loads, in city-cycle conditions
- Specially designed for Peugeot-Citroen group

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL GENESIS SPECIAL C2 0W-30
Density at 15 °C, kg/m ³	DIN 51575	840
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445 / GOST 33 / GOST R 53708	14
Viscosity index	ASTM D2270 / GOST 25371	166
Cold Cranking Viscosity at -35 °C, CCS, mPa·s	ASTM D5293 / GOST R 52559	5 809
Total Base Number, mg KOH/1g oil	ASTM D2896 / GOST 30050	5,1
Flash Point, COC, °C	ASTM D92 / GOST 4333	>220
Pour Point, °C	GOST 20287 B / ASTM D97	<-42

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".